





FEATURES:**Applications**

Bezel / In-Surface

Standard Finishes


Silver Pearl	
Gloss White	
Black	
Brushed Aluminum	

**Specifications**

- 2 - 15A, 120VAC Tamper Resistant Receptacles
(TR Embossed on Receptacle)
- 2 - 2.1A/10.5W USB Charging Ports
- Compatible with DaisyLink 4 Wire 2 Circuit Starter & Interconnecting Cables and Accessories
-
- Recommended Table Thickness: 0.25" - 2"
- Recommended Table Cutout: 2.0" x 5.25" (Reference Installation Sheet for details)
- ETL Listed for US and Canada

Dimensions

- Cove TR 2 Power, 2 USB Standard Dimensions: 6.50" x 2.50" x 3.71"



Cove TR 2 Power 2 USB
DaisyLink

DESCRIPTION	FINISH/ LENGTH	PART NUMBER
Cove™ TR - DaisyLink		
<ul style="list-style-type: none"> 2 power, 2 USB, Circuit 1 	Black Silver Pearl Gloss White Brushed Aluminum	COV-TR-2U-41-B COV-TR-2U-41-S COV-TR-2U-41-GW COV-TR-2U-41-AL
Replace "1" with "2" to specify Circuit 2. See DaisyLink Starter and Interconnecting Cable Options Below.		

DaisyLink Starter & Interconnecting Cable Options		
<ul style="list-style-type: none"> Female/Female Interconnecting Cable 	12" -180" Cable	42-FF-Length*
<ul style="list-style-type: none"> Female/Male Interconnecting Cable 	12"-180" Cable	42FM-Length*
<ul style="list-style-type: none"> Hardwire Starter Cable 	12"-180" Cable	42SB2-Length*
<ul style="list-style-type: none"> T-Connector used to branch into different direction 	Black	Daisy-T
<ul style="list-style-type: none"> DaisyLink Nylon Black Cable Covers - Add "B" to cabling part number 	Black	Cable Covers "B"
Specify in increments of 1" Cable Lengths in Part Number. Cable Lengths Minimum of 12" - 180" Maximum.		

Cove™ Bracket Accessory		
<ul style="list-style-type: none"> Optional Cove Mounting Bracket for Table Thicknesses up to "1.50" 	Black	COV-1.5-BRKT