

OASIS™ MINI - DAISYLINK

FEATURES:

Applications

Bezel / In-surface
Table-trough
Conference/Meeting Applications

Standard Finishes

Silver Pearl
Black
Brushed Aluminum
Black Brushed Aluminum




Specifications


- 4 or 6 - 15A, 120V AC Power Receptacles
- 2- 2.1A/10.5W USB Charging Ports (Available on USB Versions Only)
- 1 - 3 Telecom Plate Knockouts - Fully Customizable (Quantity Vary by Configurations; Purchased Separately)
- Compatible with DaisyLink 4 Wire 2 Circuit System - Starter & Interconnecting Cables (Purchased Separately)
- Starter & Interconnecting Cable Lengths: Minimum 12" - 180" (Specify in 1" Increments)
- Circuit 1 & 2 Options Available
- Optional Outer Pan Accessory (Purchased Separately)
- 15" Trough
- Recommended Table Thickness: 0.88" - 2"
- Recommended Table Cutout: 14.12" x 8.25" - See Install Sheet for Additional Undercuts Required
- Power Inserts UL Listed for US and Canada

Dimensions


- Oasis™ Mini Standard Dimensions: 9" x 15"
- Oasis™ Mini Inserts: 11.25" x 2.67"
- Outer Pan Dimensions: 12.20" x 15" x 5.29"



Oasis™ Mini Version USB Shown



Power, Data & USB Inserts Shown



Outer Pan

DESCRIPTION

Oasis™ Mini- DaisyLink

- Oasis Mini, 15" Trough with 6 Power Receptacles and 2 Telecom Plate Knockouts DaisyLink
- Oasis Mini 15" Trough with 4 Power Receptacles and 3 Telecom Plate Knockouts DaisyLink
- Oasis Mini, 15" Trough with 6 Power Receptacles, 2 USB Charging Ports, and 1 Telecom Plate Knockout DaisyLink

FINISH

Silver Pearl/Aluminum
Black/Black Aluminum
Silver Pearl
Black

Silver Pearl/Aluminum
Black/Black Aluminum
Silver Pearl
Black

Silver Pearl/Aluminum
Black/Black Aluminum
Silver Pearl
Black

PART NUMBER

OAM-A-4-1-S
OAM-A-4-1-B
OAM-A-PC-4-1-S
OAM-A-PC-4-1-B

OAM-B-4-1-S
OAM-B-4-1-B
OAM-B-PC-4-1-S
OAM-B-PC-4-1-B

OAM-U-4-1-AL
OAM-U-4-1-BA
OAM-U-PC-4-1-S
OAM-U-PC-4-1-B

Replace "1" in Part Number with "2" for Circuit 2 Options. See Starter and Interconnecting Cable Options Below.

DaisyLink Starter & Interconnecting Cable Options

- Female/Female Interconnecting Cable 12" -180" Cable 42-FF-Length*
- Female/Male Interconnecting Cable 12" -180" Cable 42FM-Length*
- Hardwire Starter Cable 12"-180" Cable 42SB2-Length*
- T-Connector used to branch into different directions Black Daisy-T
- DaisyLink Nylon Black Cable Covers - Add "B" to cabling part number Black Cable Covers "B"

Specify in increments of 1" Cable Lengths in Part Number. Cable Lengths Minimum of 12" - 180" Maximum.

Accessories - For Oasis Mini & Mini UT Versions

- Oasis-Mini Outer Pan - for concealing underside of 15" Oasis Mini trough Silver Pearl/Black OASIS-MINI PANS OASIS-MINI PAN

Telecom Plates, Lids & Bezel sold separately. "Build Your Own" Configurations Available - Call for Customization