

ISLE™ G2 SERIES CORDED



FULLY LOADED POWER HUB

PORTARIE CHARGING POWER FROM EVERY ANGLE

Give transitional and collaborative spaces a much needed boost of connectivity. As a free standing, full-service, power and charging station, Isle™ G2's dynamic functionality provides 360° of power, USB and USB-C® charging capabilities for multi-user connection. Environments like airport terminals, student unions, and hotel lobbies can now offer a surplus of innovative and flexible power like never before.



FEATURES:

Mounting Capabilities

Freestanding

Portable

Applications

Collaborative Spaces

Floor Surfaces

Standard Finishes

Silver



White



Black Bronze



Latte Carbon







CORDED (POWER WITH USB-A & USB-C CONFIGURATION SHOWN)

SPECIFICATIONS:

- 15A/120V AC Tamper-Resistant Receptacles
- (1) 55W USB-C Power Delivery port with GaN technology and (1) 1.5A, 5V USB-A port OR
 - (2) USB-C port configurations, (1) 55W USB-C Power Delivery port with GaN and (1) USB-C Convenience port with 1.5A, 5V output
- Standard Cord Length: 108"
- Integrated Cord Management Wrap Cord Base of Unit
- Approximate Weight: 28 lbs.
- ETL Listed for US and Canada

USB Type-C* and USB-C* are registerted trademarks of USB Implementers Forum



Free-Standing Portability (Featured to the right) -

This portable multi-purpose power tower can be placed anywhere charging capabilities are needed. Simply move and position one among a cluster of chairs or tables in a lounge, student center, or meeting area. Should the space configurations change, move the Isle G2 and reposition in the new space.









Tether/Anchor to Surface (Featured to the left) -

Additional slots located underneath the base of the unit allow $Isle^{TM}$ G2 to either tether or bolt to surface should mobility not be desired.

SERIES DIMENSIONS



12 POWER RECEPTACLES
3 USB PORTS
3 USB-C PORTS



12 POWER RECEPTACLES 6 USB-C PORTS;

Ordering information continued on following page...

PART NUMBER CONVERSION

Old Part Number	New Part Number		
Silver			
ISL-12U6C-S108	305304.05.25.09		
ISL-12U3AC-S108	305304.03.25.09		
White			
ISL-12U6C-GW108	305304.05.VW.09		
ISL-12U3AC-GW108	305304.03.VW.09		
Black			
ISL-12U6C-GB108	305304.05.04.09		
ISL-12U3AC-GB108	305304.03.04.09		
Bronze			
ISL-12U6C-Z108	305304.05.28.09		
ISL-12U3AC-Z108	05304.03.28.09		
Latte			
ISL-12U6C-L108	305304.05.31.09		
ISL-12U3AC-L108	305304.03.31.09		
Carbon			
ISL-12U6C-C108	305304.05.34.09		
ISL-12U3AC-C108	305304.03.34.09		



CORDED CONFIGURATIONS

CHOOSE YOUR FINISH:

SELECT YOUR POWER:



Power	USB-A	USB-C [®]
Receptacles	PORTS	PORTS

POWER & USB-C® | STANDARD 108" CORD - SILVER

. O E	- - 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,		TID SIEVER
12	-	6	305304.05.25.09
POWER, USB & USB-C* STANDARD 108" CORD			
12	3	3	305304.03.25.09





Power	USB-A	USB-C [®]
Receptacles	PORTS	PORTS

POWER & USB-C® | STANDARD 108" CORD - WHITE

12	-	6	305304.05.VW.09	
POWER, USB & USB-C® STANDARD 108" CORD				
12	3	3	305304.03.VW.09	





Power	USB-A	USB-C [®]
Receptacles	PORTS	PORTS

POWER & USB-C® | STANDARD 108" CORD

	12	-	6	305304.05.04.09
POWER, USB & USB-C® STANDARD 108" CORD				
	12	3	3	305304.03.04.09



CHOOSE YOUR FINISH:

SELECT YOUR POWER:



Power	USB-A	USB-C [®]
Receptacles	PORTS	PORTS

POWER & USB-C® | STANDARD 108" CORD - BRONZE

12	-	6	305304.05.28.09	
POWER, USB & USB-C® STANDARD 108" CORD				
12	3	3	305304.03.28.09	






Power	USB-A	USB-C [®]
Receptacles	PORTS	PORTS

POWER & USB-C® | STANDARD 108" CORD - LATTE

12	-	6	305304.05.31.09	
POWER, USB & USB-C® STANDARD 108" CORD				
12	3	3	305304.03.31.09	





POWER & USB-C® | STANDARD 108" CORD - CARBON

12	-	6	305304.05.34.09
POWER, USB & USB-C° STANDARD 108" CORD			
12	3	3	305304.03.34.09

